BOLT-234CGS

2MP Color MIPI Camera based on Onsemi AR0234 Sensor

Vadzo Bolt-234CGS is a Full HD MIPI Camera based on Onsemi AR0234 Sensor coupled with high-performance ISP. The camera delivers max resolution of 2MP and Video streaming of 1080p, 720p and VGA. Applicable in use cases such as robotics camera, AGV camera, drone camera, traffic monitoring camera, security camera, video surveillance camera, etc. Bolt-234CGS has been integrated with solutions based on platforms such as Raspberry PI, Nvidia Nano, Nvidia XavierNX, etc.

Key Features

- Sensor Model: AR0234 Onsemi Sensor
- Max Resolution: 2MP
- Pixel: 3.0 µm x 3.0 µm
- Shutter: Global Shutter
- Lens FOV: 76 DFOV
- Compliance: RoHS 3, REACH



Applications

- **Warehouse Robotics:** Object Scanning, Document Scanning, OCR, Obstacle Detection.
- **Smart Surveillance:** Facial Recognition, Day/Night Video Recording, Smart Parking, Pedestrian Safety.
- **Retail Analytics & Automation:** Inventory Monitoring, Age Verification, Demography Analysis, Shelf Monitoring, Self-Checkout.

INDEX

1. Introduction 3
2. Camera Specifications 3
3. Supported Resolutions 4
4. Supported Camera Functions 5
5. MIPI Interface 5
6. Status LED 5
7. Temperature and Humidity Specifications 6
8. Dimensions 6
Board Top Side – 2D 6
ATR Board 2-Lane Bottom Side – 2D 6
ATR Board 4-Lane Bottom Side – 2D 7

Copyright © 2017-2026 Vadzo Imaging

1. Introduction

Bolt-234CGS is a MIPI Fixed-Focus Global Shutter color camera based on Onsemi AR0234 sensor. The camera incorporates the AR0234 Bayer sensor from Onsemi integrated with an on-board Image Signal Processor (ISP) to perform functions such as debayering, demosaicing, color correction, contrast correction, gamma correction, denoising, lens corrections and so on.

In addition to this, the ISP also supports Auto functions such as Auto-Exposure and Auto-White Balance. This is a two-board camera solution that comprises of the camera module board and the adapter board. There are two variants of the adapter board to 2-Lane MIPI CSI 2 as well as 4-Lane MIPI CSI 2 interfaces.

2. Camera Specifications

General Information	
Product Family	Bolt series
Camera Model	Vadzo Bolt-234CGS
Sensor	
Sensor	AR0234 sensor from Onsemi
Sensor Format	1/2.6”
Pixel Size	3.0 µm x 3.0 µm
Max Resolution	2MP – 1920(H) x 1200(V)
Shutter	Global Shutter
Chroma	Color
Camera Data	
Interface	2-Lane MIPI CSI 2 & 4-Lane MIPI CSI 2
Pixel Depth	8bit / 10bit
Output Format	YUV422
Exposure Control	Manual Control via software & Auto-Exposure
GPIO	2 x NC
Camera Hardware	

Copyright © 2017-2026 Vadzo Imaging

Lens	S Mount (M12 Standard)
MIPI connector	686115148922 (2 Lane) & F305-1A7H1-21022-E100 (4 Lane)
Power Requirement	Max: 1.45 W at 3.3VDC Min: 0.80 W at 3.3VDC
Operating Temperature	-40^{0}C to 85^{0}C
Dimension	38mm (L) x 38mm (B) convertible to 32mm (L) x 32mm (B)
Weight	13 Grams (Without Lens)
Camera Software	
Video Resolutions	VGA, HD, and FHD
Video formats	YUV422
Still Image Resolutions	VGA, HD, and FHD
Image Capture formats	BMP
Image Capture Modes	Software trigger
Camera Controls	Brightness, Exposure, Contrast, Sharpness, Saturation, Gamma, Gain, White Balance, Denoising
Conformity	
Conformity	RoHS 3, REACH

3. Supported Resolutions

Resolution	**Frame Rates (FPS) in 2-Lane MIPI CSI 2**	**Frame Rates (FPS) in 4-Lane MIPI CSI 2**
	YUV422	**YUV422**
640 x 480 (VGA)	120	120
1280 x 720 (HD)	60	120
1920 x 1080 (FHD)	40	60
1920 x 1200 (Full)	40	60

Copyright © 2017-2026 Vadzo Imaging

4. Supported Camera Functions

The List of functions supported by the Bolt-234CGS camera are:

- Resolution Control
- Image Format Setting
- Video Format Setting – YUV422
- Image Capture Software Trigger
- Gain – Auto & Manual
- Exposure – Auto & Manual
- White Balance – Auto & Manual
- Anti Flicker – 50Hz/60Hz
- Contrast Control
- Gamma Control
- Hue & Saturation Control
- Sharpness Control

5. MIPI Interface

The camera module supports both 4-Lane MIPI CSI 2 as well as 2-Lane MIPI CSI 2 interface. Vadzo has designed the camera hardware such that it can be directly integrated with Raspberry PI as well Nvidia Jetson development kit via the 2-Lane MIPI CSI 2 interface. Vadzo has used the 686115148922(2 Lane) from Wurth Elecktronik for this interface.

Vadzo has Integrated the capability of functioning in the 4-Lane MIPI CSI 2 bandwidth as well to ensure that you can achieve faster frame rates. Vadzo has used the F305-1A7H1-21022-E100(4 Lane) from Amphenol for this interface

6. Status LED

Status LED's indicate the below:

- Red color indicates Device is powered ON with no Streaming.
- Yellow color indicates: Camera is currently Streaming.


Copyright © 2017-2026 Vadzo Imaging

7. Temperature and Humidity Specifications


Description	Specification
Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
Humidity	20% to 80%, Relative, non-condensing.

8. Dimensions

Board Top Side – 2D




ATR Board 2-Lane Bottom Side – 2D



Copyright © 2017-2026 Vadzo Imaging

ATR Board 4-Lane Bottom Side – 2D



IMPORTANT NOTICE AND DISCLAIMER

Vadzo Imaging products are sold by description only. Vadzo Imaging reserves the right to change the information in this document, including URL references and/or specifications is subject to change without notice. Customers should obtain the latest relevant information and data sheets before placing orders and should verify that such information is current and complete.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

THIS DOCUMENT IS PROVIDED AS IS WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION, OR SAMPLE.

All liability, including liability for infringement of any proprietary rights, relating to the use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

All trade names, trademarks, and registered trademarks mentioned in this document are the property of their respective owners and are hereby acknowledged.

Copyright © 2017–2026 Vadzo Imaging. All Rights Reserved.